

FCT Fixed Cellular Terminal

GSM Gateway to convert SIM to Landline Connection

CCL



FCT
Single SIM Gateway

Features

- ✓ Single SIM Gateway
- ✓ Connects to 2G/3G/4G SIM (except Jio)
- ✓ Generates a normal Telephone Line from a GSM SIM.
So, one can dial out or receive mobile calls from conventional telephone set
- ✓ Can be connected to a PBX or directly to a Telephone Set
- ✓ STD Code Addition : In direct local dialing, no need to pre-fix area code

Technical Specifications

| | |
|---------------------------|--|
| Operating Voltage | : 12V DC, 1A |
| Standby Current | : 130mA to 170mA |
| Current during Talk | : 320mA to 410mA |
| GSM Module | : Quad Band - GSM 850/ 900/ 1800/ 1900 MHZ Operating Volatge:3.3~4.6V 4.0V Support SIM Card: 1.8V/3.0V |
| SIM Slot | : A Slot (Standard Type) |
| Mounting Type | : Wall Mount |
| Max. Loop Current | : 30mA |
| Max. Loop Resistance | : 1,250 Ohms |
| Caller ID Generation Mode | : DTMF |
| Ambient Conditions | : 0 to 45°C, up to 95% Non-Condensing humidity |

Designed, Developed & Manufactured in India

Model available for Dual SIM also

ISO: 9001 2015 Certified Company

Copper Connections Limited

B-221, Okhla Industrial Area, Phase-I, New Delhi-110020

Ph: 011-40625543 Email: cclmailccl@gmail.com www.copperconnections.com