

PBX

Digital Series



Up to 504 Ports & 2-PRI interface

Features

- | | |
|---|---|
| <ul style="list-style-type: none"> Expandable up to 504 Ports CO Lines - Maximum 96 PRI Line Interface - Maximum 2 KTS Extensions - Maximum 32 VOIP Solutions Available Auto Attendant messages for two concurrent Telephone Calls <ul style="list-style-type: none"> • Welcome Message • Extension Busy Message • No Answer Message • Wrong Number Dialed Message Non-Blocking Architecture: Communication on all ports can take place simultaneously CTI Port for Computer Telephony Interface with Third-Party Software Alarm Auto Call Back Auto Call Disconnection Barge-In Battery Charger for operation during power failure Boss Secretary Call Call Details / Call Billing / Call Recording / Hotel Management through Computer Call Forwarding – in 3 different conditions | <ul style="list-style-type: none"> Call Pick-Up Call Parking CLI – Transferable + Internal (DTMF / FSK) Conferencing Day / Night Mode Do Not Disturb (DND) Door Phone – 1 or more Door Lock – 1 or more Flash Time setting Flexible numbering Follow me Hold Music with provision to connect external source Hot Line to Junction or Extension Incoming Telephone Ring Assignment in Simultaneous / Round Robin mode Telephone Line Access during Power failure Telephone Line Dialing Control: Allow/Disallow ISD, STD, Local numbers Telephone Line Grouping Memory Dialing Paging Redial Walking class of service |
|---|---|

Note : All features are not part of basic system. Some are optional.

PBX Digital Series

Models & Capacity				
Model	Ports	KTS (Max.)	PRI	Description
DG 120	120	32	-	The ports can be a combination of CO Lines, SLT Extensions & KTS Extensions
DG 504	504	32	-	
DG 250	248	32	Up to 2	With 1 PRI, no. of ports= 216 With 2 PRI, no. of ports= 184

Technical Specifications

Switching	:	PCM/TDM
Speech Path	:	Non-Blocking
Extension Loop Resistance	:	Less than 1,200 Ohms
Junction Loop Resistance	:	Less than 1,200 Ohms
Crosstalk	:	Better than 70 dB
Insertion Loss	:	Less than 1 dB
Extension Voltage	:	24V / 48V selectable
PRI Interface	:	Up to 2 PRI Lines
Computer Interface	:	Serial Port-2
Input Voltage	:	220VAC +/- 10% at 50 Hz
Battery	:	24 Volts DC (7 A.H.)
Cabling	:	One pair cable for Telephone Set or KTS
Ambient Conditions	:	0 to 40 Deg C & up to 90% humidity

Copper Connections Limited

B-221, Okhla Industrial Area, Phase-I, New Delhi-110020. Ph.: +91-11-40625543
cclmailccl@gmail.com www.copperconnections.com